

KABEL COAX GETI 125CU PE 7mm BLACK 100m



Ocjena: Nije još ocjenjeno

Cijena

Cijena: 90,00 €

[Postavite pitanje o ovom proizvodu](#)

Opis

- inner conductor: pure copper, \varnothing 1,00mm \pm 0,01
- first screen: overlapped Cu foil: \varnothing 4,87mm \pm 0,05
- second screen: bare copper, 72 x 0,10m
- braid diameter: 5,27mm \pm 0,05
- dielectric: \varnothing 4,80mm \pm 0,05
- sheath: PE black, \varnothing 6,8mm \pm 0,10
- nominal impedance: 75 Ω \pm 3
- capacity: 55 pF / km \pm 2
- maximum voltage: 2kV
- return loss: > 20 dB (5-2500 MHz)
- minimum static bend radius: 70mm
- velocity ratio: 81% (+/-2)
- operating temperature: -30 $^{\circ}$ C \pm 60 $^{\circ}$ C
- storage temperature: -30 $^{\circ}$ C \pm 70 $^{\circ}$ C
- packaging: 100 m reel = 1pc
- packing quantity: 2pcs carton box

Attenuation MHz / dB / 100 m:

- 5MHz - 1.4dB
- 50MHz - 4.3dB
- 100MHz - 6.0dB
- 200MHz - 8.3dB
- 400MHz - 12.0dB
- 600MHz - 14.8dB
- 800MHz - 17.3dB
- 1000MHz - 19.6dB

- 1350MHz - 22.6dB
- 1750MHz - 26.0dB
- 2150MHz - 29.3dB
- 2400MHz - 31.3dB

Technical parameters

Use: outdoor

Attributes required: 100% copper, copper shielding, double shielding

Wire diameter: 6,8mm

Packaging: 100m

Recenzije

Trenutno nema recenzija za ovaj proizvod.