

IZLAZNI 4ETVEROSTRUKI MODULATOR PAL/CI TDX051



Ocjena:Nije još ocijenjeno
Cijena
Cijena: 922,42 €

[Postavite pitanje o ovom proizvodu](#)

Opis

PAL output module [DVB-S/S2] - Quad CI. Any of the services coming from the TDX Pool can be modulated to an analogue PAL signal. It is possible to send out 24 PAL services/TV programs from one cabinet. Each of the output modules can be delivered with 2 CI-slots.Full band modulator.

5702664920513	
Physical	
Dimensions product (H x D x W)	24 x 162 x 185 mm
Connectors	
Output connector	F-konektor
Frequency range	
Output frequency range	47 - 862 MHz
Outputs	
TV-norm	PAL (B/G, I, L, DK), SECAM
TV System	VSB VHF/UHF mono, A2, Nicam
Channel Raster	7,8 MHz
Frequency step	250 kHz
Picture carrier stability	< ±30 kHz
Spurious Signals	< -60 dB

IZLAZNI ？ETVEROSTRUKI MODULATOR PAL/CI TDX051

Output level adjusting

+3 ... -17 dB

Output Level System

103.0 dB μ V

Output impedance

75 ？

Output Return Loss

> 10 dB

Differential Gain

< 8 %

Differential Phase

< 8 ？

Group delay

< 80 ns

Output Video S/N Ratio

？ 57 dB

Sound sub carrier

5.5 / 5.74 / 6.0 / 6.5 MHz

Sound sub carrier stability

Nicam/A2: $\pm$ 1 kHz, mono: $\pm$ 5 kHz

Output Audio S/N Ratio

50 dB

CI slots

2

Power supply

Power supply current

1800 mA

Power supply voltage

12 $\pm$ 1 V

Recenzije

Trenutno nema recenzija za ovaj proizvod.