MODULATOR EDISION HDMI 3in1 pro





Ocjena:Nije još ocjenjeno
Cijena
Cijena: 150,00 €

Postavite pitanje o ovom proizvodu

Opis Technical features: - Digital single-channel HDMI Modulator to DVB-T, DVB-C or ISDB-T with HDMI loop-through & IR Tx - INPUT signal: 1x HDMI v1.4a - RF OUTPUT signal: 1 x Digital Terrestrial DVB-T, ISDB-T or Cable DVB-C MPEG4 - Frequency Range DVB-T: VHF (CH.5-12) & UHF (CH.21-69) - Frequency Range ISDB-T: VHF (CH.7-13) & UHF (CH.14-69) - Frequency Range DVB-C: 47-862 MHz - With RF loop-through - With HDMI loop-through - IR control over coaxial ready, through the embedded IR Transmitter - High Video Resolution up to FULL HD 1080p 60FPS - RF Output Level: Factory default 90 db?V, with adjustable gain up to +6db?V or attenuation up to -14db?V - MER more than 35dB - Symbol Rate: up to 31.668 MBPS - Bandwidth: 6MHZ, 7MHZ, 8MHZ - Video Encoder MPEG1, MPEG2 MP@HL , MPEG4 SP@L3 to ASP@L5, MPEG4 AVC HP @level4.1, MP@level4.1 - Audio encoder MPEGI L1/2, MPEGII LII, AAC LC, HE-AAC v1/v2 (2-CH) - Processor System: 800MHz 32Bit ARM9 CPU - Memory DDRIII 16bit 1GBit/s (Embedded) & NOR Flash 32Mbit - Fast Pre-Config Function / 50 IDs Selectable - Backup Config File by USB (CFG) - Software Upgrade by USB - Ports: RF IN, RF OUT, IR OUT, USB, HDMI IN, HDMI OUT, DC 5V/2.0A, GROUND - LCD Display with Standby function - 6 Front panel buttons: Lock, Menu/OK, Left, Right, Up, Down General: - Power Supply: 100 - 240 AC 50/60Hz - Input Voltage: DC 5V 2.0A - Power Consumption: max. 10.0W - Operating Temperature: 0°C ... +50°C - Storage Temperature: -20°C ... +70°C - Humidity Range: 10% ... 85% RH, non-condensing - Dimensions: 164x106x41 mm - Weight: 0,7 kg

Recenzije

Trenutno nema recenzija za ovaj proizvod.