MODULATOR EDISION HDMI 3in1 QUAD

Ocjena:Nije još ocjenjeno
Cijena
Cijena: 520,00 €

Postavite pitanje o ovom proizvodu

Opis Technical features: - Digital quad-channel HDMI Modulator to DVB-T, DVB-C or ISDB-T - INPUT signal: 4x HDMI v1.4a - RF OUTPUT signal: 2 x Digital Terrestrial DVB-T, ISDB-T or Cable DVB-C MPEG4 - Frequency Range DVB-T: VHF (CH.5-12) & UHF (CH.21-69) - Frequency Range ISDB-T: VHF (CH.7-13) & UHF (CH.14-69) - Frequency Range DVB-C: 47-862 MHz - High Video Resolution up to FULL HD 1080p 60FPS - RF Output Level: Factory default 90 db?V, with adjustable gain up to +6db?V or attenuation up to -14db?V - MER more than 35dB - Symbol Rate: 6MHZ: Up to 2x8000 MBPS, 7MHZ: Up to 2x9000 MBPS, 8MHZ: Up to 2x10000 MBPS - Bandwidth: 6MHZ, 7MHZ, 8MHZ - Video Encoder MPEG1, MPEG2 MP@HL , MPEG4 SP@L3 to ASP@L5, MPEG4 AVC HP @level4.1, MP@level4.1 - Audio encoder MPEGI L1/2, MPEGII LII, AAC LC, HE-AAC v1/v2 (2-CH) - Processor System: 4x 800MHz 32Bit ARM9 CPU - Memory 4x DDRIII 16bit 1GBit/s (Embedded) & NOR Flash 32Mbit - Fast Pre-Config Function / 50 IDs Selectable - Backup Config File by USB (CFG) - Software Upgrade by USB - Ports: 4x HDMI IN, RF OUT, 4x USB, SERVICE PORT, DC 12V/4.5A, GROUND - Four (4) x 4-digit LED displays - Four (4) x 6-display buttons: Menu/OK, Left, Right, Up, Down General: - Power Supply: 100 - 240 AC 50/60Hz - Input Voltage: DC 12V 4.5A - Power Consumption: max. 20.0W - Operating Temperature: 0°C ... +50°C - Storage Temperature: -20°C ... +70°C - Humidity Range: 10% ... 85% RH, non-condensing - Dimensions: 255x195x40 mm - Weight: 1,64 kg - Color: black

Recenzije

Trenutno nema recenzija za ovaj proizvod.